

# Kodak T-MAX 400

Kodak Developer	Small Tanks / Petites Cuves / Entwicklungsdozen / Små tankar / Tanques Pequeños / Svilupatrice a Spirale / Kleine Tanks				Exposure Index
	18°C	20°C	22°C	24°C	
T-Max RS	—	7	6	5	400
T-Max	—	7	6 <sup>1/2</sup>	6	400
D-76	9	8	6 <sup>1/2</sup>	5 <sup>1/2</sup>	400
D-76 (1+1)	14 <sup>1/2</sup>	12 <sup>1/2</sup>	10	9	400
HC-110 (Dil.B)	6 <sup>1/2</sup>	6	5	4 <sup>1/2</sup>	320
Microdol-X	12	10 <sup>1/2</sup>	8 <sup>1/2</sup>	7 <sup>1/2</sup>	200
Microdol-X (1+3)	—	—	18 <sup>1/2</sup>	16	320

## Push Processing / Traitement Poussé / Empfindlichkeitssteigernde Entwicklung / Pressad framkalling / Procesado Forzado / Trattamento Spinto / Geforceerd Ontwikkelen

Kodak Developer	20°C	24°C	20°C	24°C	24°C
	EI 800		EI 1600		EI 3200
T-Max RS	7	5	10	7	9 <sup>1/2</sup>
T-Max	7	6	10	8	9 <sup>1/2</sup>
D-76	8	5 <sup>1/2</sup>	10 <sup>1/2</sup>	7	—
HC-110 (Dil B)	EI 640		EI 1280		
	6	4 <sup>1/2</sup>	8 <sup>1/2</sup>	6	