

KODAK PROFESSIONAL TRI-X 400 Film / 400TX

KODAK PROFESSIONAL TRI-X 400 Film / 400TX replaces KODAK TRI-X Pan Film, and requires a different development time.

| KODAK Developer or Developer and Replenisher* | NEW Development Time in Minutes Small-Tank Processing (Agitation at 30-Second Intervals)** | | NEW Development Time in Minutes Large-Tank Processing (Agitation at 1 Minute Intervals)† | | —OR— PROFESSIONAL TRI-X 400 Film/400TX requires different development than TRI-X Pan Film. Change development time by†† |
|---|--|-------------|--|-------------|---|
| | 20°C (68°F) | 24°C (75°F) | 20°C (68°F) | 24°C (75°F) | |
| T-MAX | 6 | 4 3/4 | Not recommended | | +1/4 minute |
| HC-110 (B) | 3 3/4 | 2 1/2 | 4 1/2 | 3 | |
| MICRODOL-X | 9 1/4 | 7 1/2 | 10 3/4 | 8 1/2 | |
| D-76 (1:1) | 9 3/4 | 7 3/4 | 11 | 8 3/4 | -1/4 minute |
| D-76 | 6 3/4 | 4 3/4 | 7 3/4 | 5 1/2 | No change |
| T-MAX RS | 4 1/2 | 3 1/2 | 5 | 4 | |
| XTOL | 7 | 4 3/4 | 8 | 5 1/2 | |